



DP 125i™ / DM 125i Digital Mailing System

Designed with flexibility in mind, the DP125i™, powered by Secap's IntelliLink™ technology represents the ultimate answer to the mailing needs of busy businesses. The latest digital technology makes processing mail quiet and efficient - the perfect office companion.



How will your business benefit

- **Future-proof mailing** - *IntelliLink™* connects Secap's DP125i™ to a secure server, via the Internet, enabling services such as postal tariff changes, software updates and advertising slogans to be downloaded quickly and effortlessly.
- **Correct value postage - every letter, every time** - The DP125i™ incorporates a 2.5kg integral weighing platform, freeing up desk space and guaranteeing that each letter or package bears the correct postage value.
- **Fast, accurate postage re-crediting** - Replenish your meter 24-hours a day with simple one-touch refills via *POSTAGE BY PHONE* - quick, secure and hassle-free.
- **Easy to use** - All controls are fully integrated on one clear control panel with user-friendly instructions to guide the operator through each stage of processing mail.
- **Streamlined processing** - Efficiently frank and seal mail pieces up to 9.5mm thick, whilst larger mail is quickly processed with self adhesive tape strips. Mailing couldn't be simpler with up to 5 presets for your most commonly used jobs.
- **Monitor postal spend** - Control postage costs with tracking and reporting for up to 25 named departmental or client accounts.
- **Strengthen your brand** - Enhance standard envelopes into eye-catching branded mail pieces with tailor made customised logos.
- **Track incoming mail** - Date and time stamping incoming post ensures mail is handled efficiently.

Technical Specifications

Physical dimensions

Length	345mm
Depth	400mm
Height	230mm
Weight	6.8 kg approximate

Speed

Up to 30 letters per minute

Material sizes

Minimum material size	76mm x 127mm
Maximum material size	330mm x 381mm
Material thickness	9.5mm (max) to 0.18mm (min)
Envelope flap depth for sealing	76 (max) to 22mm (min)

Operating features

Slogan and town circle download (by modem)

2.5kg integrated weighing platform

Auto-dating

Water level indicator

Seal only/no seal modes

Low postage warning

High value protection

Original value resetting

Low ink warning

Password security

PC interface

5 job presets

Up to 25 accounts

Electrical

100-240 V, 50/60 Hz, 3A

Noise

55dB

Connectivity requirements

Connects to a standard analog phone line



Available from your authorised Secap dealer:

Total Postweigh International Ltd
1 Skelgillside
Alston
Cumbria CA9 3TR

Tel: 01434 381182

Fax: 01434 382035

Email: sales@postweigh.com

Web: www.postweigh.com